

TECHNICAL INFORMATION

Series 150

Subject	Details	
Type of Gas	Natural Gas (NG) or Propane (LPG)	
Vent	5/8" Direct Vent	
Heat Barrier	Screen (standard) or Double Glass (optional)	
Interior Design Media	Wood Style	Log Set with Embers: Charred Oak Clay Logs Split Oak Ceramic Fiber Logs Driftwood Logs
		Mixed Long and Short Branches with Embers
	Ceramic Fiber Stones	Colors: Grey or White
		Size: Large or Small
	Polished Ceramic Glass	Colors: Amber, Black, Blue and Clear
General Note	Leave 20% of burner and grill uncovered by media	
Weight	Clear 150	590 lbs.
	Clear 150 H	590 lbs.
	Clear 150 RS/LS	485 lbs.
	Clear 150 TS	485 lbs.
	Clear 150 Tunnel	452 lbs.
	Clear 150H Tunnel	452 lbs.
	Space Creator 150	487 lbs.
	Stand Alone 150	544 lbs.
Standard	Safety	ANSI Z21.88/CSA 2.33-2014
	Efficiency	ANSI P.4.1-09
Operation	Mertik Maxitrol Remote Control (full automatic, wall control unit is optional), electronic ignition	
Electrical Requirements	All models are provided with an AC adapter which requires a 110 volts 20-amp outlet. For H Series, the ac adapter does not need to be used as the interior lighting feature in the models are equipped to provide power to the receiver. Double glass and Power Vent features require an additional 2 nd and 3 rd outlet.	

Product Specifications

The fireplace has been certified for use with either Natural Gas (NG) or Propane Gas (LPG).

All Ortal fireplaces operate with a direct vent, balanced flue venting system. A direct vent gas fireplace is room-sealed using a glass front. The flue uses natural ventilation to pull air in from and release exhaust gases to the outside. For indoor installation they must be installed maintaining required clearances. Refer to manual for clearance distances. Installation is recommended in living spaces such as bedrooms, living rooms, great rooms, etc.

The fireplace must be properly connected to a venting system.

The fireplace must be installed according to Ortal USA requirements in addition to any local codes that may apply. If none exist, then the current CSA installation code must be followed:

- USA, ANSI Z223.1/NFPA 54
- Canada, CSA B149

Gas Pressures & Power Output

Models	Gas	Inlet Pressures		Manifold Pressures		Heat Output	
		Min.	Max.	Min.	Max.	Min.	Max.
Clear 150, Clear 150H, Clear 150 RS/LS, Clear 150 TS, Clear 150 Tunnel, Clear 150H Tunnel, Space Creator 150, Stand Alone 150	Natural Gas (NG)	7.0" WC	7.0" WC	0.9" WC	3.5" WC	23,300 BTU/hr	43,700 BTU/hr
	Propane (LPG)	11.0" WC	11.0" WC	5.8" WC	10.7" WC	27,100 BTU/hr	36,900 BTU/hr

Parts Included:

- Ortal fireplace box
- Ceramic Glass Panel
- Screen barrier comes standard with every model but may be substituted with the Double Glass feature.
- Choice of Ortal interior media, choose one or mix from these options:
 - Ceramic fiber stones (Grey or White – Large or Small)
 - Long and short branches with beige embers
 - Log set with beige embers (Charred Oak Clay, Split Oak Ceramic Fiber and Driftwood)
 - Polished Ceramic Glass (Clear, Black, Blue and Amber)
- Ortal burner (sizes vary based on fireplace selection)
- Mertix GV60 combination control valve, Mertix Maxitrol GV60 ignition and control system (wireless remote control with battery and receiver) for LPG or NG
- Spark/pilot/thermal coupling unit
- 10mm ratchet wrench
- Mounting brackets
- Full set of flue restrictors
- AC adapter (Electrical requirement: 110 volts 20-amp outlet)